

**Declaration of Performance**  
**No. FLAM\*\*13\*\*1200BA\*\*1\_2016**



In accordance with Construction Products Regulation 305/2011 regarding the harmonization for the marketing of construction products and repealing Council Directive 89/106/EEC, the manufacturer (point 4) declares on his sole responsibility that the performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 7 and the product can be used according to the instructions contained in the product documentation.

**1. Unique identification code of the product-type**

**GYPSUM PLASTERBOARD NIDA FLAM, TYPE F, TAPERED EDGES**  
**THICKNESS 12.5 mm, FIRE REACTION : A2-s1,d0(B1)**

**2. Product Identification**

(type, serial number or any other element allowing identification as required pursuant to Article 11(4) )

**Type, date and hour of manufacturing, printed on the back of the boards**  
**Name, package number, printed on package label**

**3. Intended use**

**According to annex B1, SR EN 520+A1:2010**

**4. Name and contact address of the manufacturer**

**Head office**

SINIAT SA

Strada Drumul Leordeni 106, sect 4, București, România

Telefon:+ 021 334 97 75

Fax: + 4 021 334 97 77

[www.siniat.com](http://www.siniat.com)

**Plant**

Strada Siniat Nr.1, Turceni, Romania

Telefon:+ 037 284 93 00

Fax: + 037 284 93 01

**5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

**System 4 for all requirements**  
**According to annex ZA.2 of reference standard**

## 6. Construction Product covered by harmonized standard:

**SR EN 520 + A1: 2010 “Gypsum Plasterboard: definitions and requirements and test methods”**

## 7. Declared performance

Essential Characteristics	Harmonized Standard	Standard requirements	Performance
Reaction to fire class	SR EN 520 +A1:2010 clause 4.2	Classification without further trials according to Annex B	A2-s1,d0 / B1
Shear strength (for stiffening timber frame external walls and timber roof truss structure)	SR EN 520 +A1:2010 clause 4.1.1	This characteristics is not subject to a threshold value	NPD ( No Performance Determined )
Water vapor permeability (dimensionless)	SR EN 520 +A1:2010 clause 4.4	Tabulated design value according to EN 12524	10
Flexural strength – CD (N)	SR EN 520 +A1:2010 clause 4.1.2	Threshold value 210	210
Flexural strength – MD (N)	SR EN 520 +A1:2010 clause 4.1.2	Threshold value 550	550
Core cohesion at high temperature (additional requirement for gypsum plasterboard type F)	SR EN 520 +A1:2010 clause 4.12	When a type F plasterboard is a subject to the test according p.5.10 /SR EN 520 +A1:2010, none of the 6 specimens shall break.	Conform
Thermal resistance ( W/mK)	SR EN 520 +A1:2010 Clause 4.7	Tabulated design value according to EN 12524	0,25
Impact resistance (in end use conditions) (kJ)	SR EN 520 +A1:2010 clause 4.3	Performance declared is for the system of which the product is a part	See producer’s literature
Direct airborne sound insulation	SR EN 520 +A1:2010 clause 4.6.1	Performance declared is for the system of which the product is a part	See producer’s literature
Acoustic absorption (in end use conditions)	SR EN 520 +A1:2010 clause 4.6.2	Performance declared is for the system of which the product is a part	See producer’s literature

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance at point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

CE marking is implemented since 2016.

- Name and address of the laboratory which performed the trials: plant laboratory

Signed for and behalf of the manufacturer:

Chemist Jianu Janina  
Laboratory Manager



Eng . Budrugaec Gheorghe  
Plant Manager



Turceni, 11.04.2016