



## Declaration of Performance (DoP)

**DoP Nº.: DP004 CIDAC / 2015-06-25**  
(According to Annex III of the Regulation (CE) n°305/2011)

Version 02 / June 2015

**1. Product Name:** **HIDROSTAN OUT**  
**Thicknesses (0.75, 1.10) mm**

**2. Product Type:**  
Number allowing identification of the construction product as required under Article 11(4) of the CPR.

(lot nº: see label and product)

**3. Intended for use** as anti-capillary barrier in buildings and the range of use is vapour control layer such as façade waterproofing or similar.

**4. Name and registered trade name**

### **CIDAC, S. COOP. R. L.**

Carretera de Sant Joan Despí, 101 -103.  
08940 Cornellà (Barcelona) SPAIN  
Tel.: +34 933 772 262 / +34 933 772 405  
Fax: +34 933 778 098  
E-mail: [info@cidac.com](mailto:info@cidac.com)  
Web: [www.cidac.es](http://www.cidac.es)

**5. AVCP:** System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

**System 3**

**6. Notified Body:** **APPLUS / LGAI Technological Center S.A (n° 0370)**

has performed type and reaction to fire tests and has issued reports.

In case of the declaration of performance (DoP) concerning a construction product covered by the harmonized standard:

**EN 13984:2007**

*Flexible sheets for waterproofing. Plastic and rubber vapour control layer.*

**EN 14909:2006**

*Flexible sheets for waterproofing. Plastic and rubber damp proof courses.*

---

CIDAC, S. Coop. R. L.; Ctra. De Sant Joan Despí, 101-103 08940-Cornellà de Llobregat (Barcelona)

Tel.: +34 933 772 262 / +34 933 772 405 Fax: +34 933 778 098

E-mail: [info@cidac.com](mailto:info@cidac.com) Web: [www.cidac.es](http://www.cidac.es)

## 7. Declared Performance:

Harmonized Technical Specification	Characteristic	Test method	Value
EN 13984 EN 14909	Reaction to fire	EN 13501-1	Class E
	Watertightness (2 kPa)	EN 1928	Pass
	Resistance to impact	EN 12691	≥ 300 mm
	Durability (alkali)	EN 1847 EN 12311-2	Pass
EN 13984	Water vapour transmission properties	EN 1931	33200 μ
	Joint Strength	EN 12317-2	≥ 200 N / 50 mm
	Tensile Strength	EN 12311-2	≥ 6.5 MPa
	Elongation at break	EN 12311-2	≥ 300%
	Tear strength	EN 12310-2	≥ 25 N
	Resistance to water vapour after artificial ageing	EN 1296 EN 1931	Pass
EN 14909	Foldability at Low Temperature	EN 495-5	≤ -30 °C
	Durability (artificial ageing) (2 kPa)	EN 1296 EN 1928	Pass

## 8. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

### Signed by:



Cornellà de Llobregat, Barcelona,

Marta Montes Pedraza (Quality Assurance)

28/05/2015