

No. SI-KP-0713135

1. Unique identification code of the product-type:

**EN 14195 – CD/27/28/27**

**EN ISO 12944 – C5**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Siniat corrosion-protected C5 ceiling-profile UD 28**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Manufacture of ceiling construction**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Siniat GmbH**  
**Frankfurter Landstraße 2-4**  
**61440 Oberursel, Germany**  
**Phone: +49 (0) 61 71 61 30 00**  
**fax: +49 (0) 61 71 61 31 55**  
**E-Mail: [fragen@siniat.com](mailto:fragen@siniat.com)**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified agency: IKS – Dresden**

No. SI-KP-0713135

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14195:2005
Yield strength	> 220 N/mm <sup>2</sup>	EN 14195:2005
Corrosion protection class	C5 M	EN ISO 12944-1-8
Class of protective coating	Z 275	EN ISO 12944-1-8
Nominal thickness	0,60 mm	EN 14195:2005
web	28,0 mm (± 0,5 mm)	EN 14195:2005
flange	27,0 mm (± 0,5 mm)	EN 14195:2005
Angular dimension	± 2°	EN 14195:2005
Length	L ≤ 3000 mm (± 3 mm) L > 3000 ≤ 5000 mm (± 4 mm)	EN 14195:2005
Twist of section	h/w < 0,1	EN 14195:2005
Straightness of the section	< L/400	EN 14195:2005
Hazardous substances	NPD	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

-

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

Oberursel, July 1st, 2013



Ulrich Horn, managing director



p.p. Werner Huber, head of department ATE